

Epic Swim Platform Mounting Instructions

First, mount the FAE (refer to FAE Installation Instructions).

The FAE was shipped with square tubing; there is 1 long square tube, 2 short square tubes, and 4 very short spacers. The 2 short square tubes run front to back (fore to aft) and attach to the swim platform using bolts and the 4 very short spacers. The long square tube runs left-right; the FAE long all-thread bolts attach to the long square tube.

1 - Drill 2 sets of holes through the 2 short square tubes. The holes are the same distance apart as the 2 bolts holding the Epic Swim Platform to the boat (orange bolts in drawing – these should be the same distance on the left and right but verify before drilling). Using the longer bolts and regular nuts supplied, and the 4 square tube spacers, loosely mount the short square tubes to the swim platform. You will need a second person to hold a wrench on the inside of the boat while re-moving and installing the swim platform bolts.

2 - Place the long square tube (blue in drawing) on top of the 2 short square tubes and position it over the red rubber hose of the FAE and mark the 2 short square tubes where the holes need to be drilled (this distance should be the same on both short tubes). Remove the short square tubes, drill the holes and then permanently attach the 2 short tubes to the swim platform (put silicone sealant on the washers above and below the swim platform).

Now position the long square tube, centered left to right; mark and drill the holes to mount to the short square tubes (green bolts in drawing). The long square tube will then have two holes drilled over the red rubber hose. This is where the all-thread bolts are connected. Bolt the long square tube to the short tubes and mount the all-thread bolt per the FAE Installation Instructions. Complete the installation by installing the Nyloc Nuts and confirming that all bolts are tightened.

